

## Specifications

FREQUENCY		
<b>Range:</b>		
LS3081P:	9 kHz to 3GHz	
LS6081P:	9 kHz to 6GHz	
LS1291P:	9 kHz to 12GHz	
<b>Resolution:</b>	0.001 Hz	
<b>Phase offset:</b>	0.01 deg	
<b>Switching speed:</b>	500 $\mu$ s	

  

FREQUENCY REFERENCE		
<b>Temp. Stability:</b>	$\pm$ 25 ppb max.	
<b>Aging:</b>	$\pm$ 3 ppm for 20 years	
<b>Warm up time:</b>	30 min	

  

AMPLITUDE		
<b>Max output power:</b>		
Settable:	+20 dBm	
Calibrated:	+15 dBm <sup>(1)</sup>	
<b>Min output power:</b>	Base	LP Opt.
Settable:	-30 dBm	-100 dBm
Calibrated:	-20 dBm	-80 dBm
<b>Resolution:</b>	0.01 dB	
<b>Power Mute:</b>	-95 dBm	
<b>Output Return Loss:</b>	-10 dBm	
<b>Accuracy (dB):</b>	-50dBm to +15dBm	-90dBm to -50dBm <sup>(2)</sup>
Up to 100MHz:	$\pm$ 0.3 (typ.)	$\pm$ 0.5 (typ.)
100MHz to 3GHz:	$\pm$ 0.4 (typ.)	$\pm$ 0.6 (typ.)
3GHz to 9GHz:	$\pm$ 0.7 (typ.)	$\pm$ 0.9 (typ.)
Above 9GHz:	$\pm$ 1 (typ.)	$\pm$ 1.5 (typ.)

  

PHASE NOISE (dBc/Hz)		
<b>Measured @ 10kHz offset</b>		
<b>1 GHz:</b>	-138 (typ.)	
<b>2 GHz:</b>	-133 (typ.)	
<b>3 GHz:</b>	-130 (typ.)	
<b>6 GHz:</b>	-124 (typ.)	
<b>12 GHz:</b>	-118 (typ.)	

  

HARMONICS (dBc)	
<b>Up to 100 MHz:</b>	-30 dBc
<b>100 MHz to 12 GHz:</b>	-50 dBc <sup>(3)</sup>

  

SUB HARMONICS (dBc)	
<b>6 to 12 GHz:</b>	-55 dBm

  

NON HARMONICS (dBc)	
<b>Up to 12 GHz:</b>	-90dBc (typ.) <sup>(4,5)</sup> -60dBc max. <sup>(6)</sup>

  

MODULATION	
FREQUENCY MODULATION	
<b>Maximum Deviation:</b>	10 MHz
Resolution:	0.1% or 1 Hz (the greater)
<b>Modulation Rate:</b>	1 MHz
Resolution:	1 Hz
AMPLITUDE MODULATION <sup>(6)</sup>	
<b>AM Depth:</b>	
Type:	Linear
Maximum settable:	90%
Resolution:	0.1% of depth
<b>Modulation rate:</b>	DC to 100 kHz
PHASE MODULATION	
<b>Peak Deviation:</b>	360 deg
<b>Modulation Rate:</b>	DC to 100 kHz
PULSE MODULATION (PLS OPTION)	
<b>On/off ratio:</b>	60 dB
<b>Rise/fall time (10%-90%):</b>	15ns (typ.)
Resolution:	6.4ns
Minimum Width:	32ns
Repetition frequency:	DC to 10 MHz
PATTERN MODULATION (PAT OPTION)	
<b>Number of steps:</b>	1 to 2048
<b>Step Repetition:</b>	1 to 65535
<b>On/off time:</b>	32 ns to 20 days

  

SWEEP	
<b>Range:</b>	Same as freq. range
<b>Modes:</b>	Frequency and amplitude
<b>Dwell time:</b>	10 $\mu$ s to 1000 s
<b>Resolution:</b>	1 $\mu$ s
<b>Number of points:</b>	2 to 65535
<b>Step change:</b>	Linear
<b>Trigger:</b>	Free run, External, Bus, Timer

  

INPUTS	
MODULATION INPUT	
<b>Connector Type:</b>	SMA
<b>Input Impedance:</b>	50 $\Omega$
<b>Max. input voltage:</b>	$\pm$ 1V
<b>Input damage level:</b>	$\pm$ 3.5V
PULSE / TRIGGER INPUT	
<b>Connector type:</b>	SMA
<b>Input Impedance:</b>	50 $\Omega$
<b>Input voltage:</b>	TTL, CMOS compatible
Threshold:	1.5V
<b>Damage level:</b>	-0.42V or 5.42V
EXTERNAL REFERENCE INPUT	
<b>Connector type:</b>	SMA
<b>Input Impedance:</b>	50 $\Omega$
<b>Waveform:</b>	Sine or Square
<b>Frequency:</b>	10/100MHz
<b>Power:</b>	-3 dBm to +10 dBm
<b>Absolute Max. Level:</b>	+15 dBm
<b>Locking Range:</b>	$\pm$ 2 ppm

  

OUTPUTS	
RF OUT	
<b>Impedance:</b>	50 $\Omega$
<b>Connector type:</b>	SMA
<b>Number of channels:</b>	1

<sup>(1)</sup> Above 25kHz; <sup>(2)</sup> With LP Option; <sup>(3)</sup> 750MHz to 900MHz -35dBc (typ.); <sup>(4)</sup> -60dBm max. @ 1GHz, 1.5GHz, 2.5GHz and 3GHz; <sup>(5)</sup> -75dBm max. @ -15dBm to +15dBm and f>6GHz  
<sup>(6)</sup> Boundary spurs which may appear @ -100MHz to +100MHz offset from CW. <sup>(6)</sup> Specified for >100MHz.

## Specifications

GENERAL	
<b>Voltage:</b>	+12.0 to +12.6 VDC
<b>Supply Voltage:</b>	+15 V DC
<b>Power Consumption:</b>	60W max. (45W typ)
<b>Display Type</b>	10", TFT capacitive touch screen
<b>Battery (included):</b>	
Type:	4-cell, replaceable
Standby:	Up to 2 hours
Max. load:	Up to 1 hours
<b>Interface:</b>	
Host:	2 x USB type A
Device:	1 x USB type B 1 x micro USB for LAN adapter
<b>Storage:</b>	Removable SD card
<b>Dimensions:</b>	280 x 225 x 65 mm (W x H x D)
<b>Weight:</b>	
Without Package:	3 kg
Shipping Weight:	4.5 kg
<b>Temperature:</b>	
Operating:	0°C to +40°C
Storage:	-40°C to +70°C
<b>Warm up time:</b>	15 minutes
<b>Humidity:</b>	85% RH, non - condensing
<b>Safety:</b>	CE Marked, IEC61010-1:2010
<b>EMC:</b>	IEC 61326-1:2013
<b>Calibration</b>	2 years
<b>Warranty*:</b>	3 year standard * 1 year standard in India

ORDERING INFORMATION	
MODEL	DESCRIPTION
LS3081P	3GHz Portable RF Analog Signal Generator
LS6081P	6GHz Portable RF Analog Signal Generator
LS1291P	12GHz Portable RF Analog Signal Generator
OPTION	
BAT	4-cell, replaceable battery (extra)
CHA	External Charger for the Lucid Portable Battery
PLS	Pulse Modulation Option
PAT	Pattern Modulation Option
LP	Low Power Option