

# MODELS WW5061/2

## 50MS/s Single/Dual Channel Arbitrary Waveform Generators

### Specification

#### CONFIGURATION

**No. of Channels:** 1/2, semi-independent

#### STANDARD WAVEFORMS

**Waveforms:** Sine, Triangle, Square, Pulse, Ramp, Sine(x)/x, Gaussian, Exponential, Repetitive Noise, DC.

#### Frequency Range:

Sine 100μHz to 25MHz  
 Square, Pulse 100μHz to 15MHz  
 All others 100μHz to 7.5MHz

#### SINE

**Start Phase:** 0 to 360°

**Phase Resolution:** 0.1°

#### Harmonics Distortion, 3Vp-p (typ.):

DC to 2.5MHz <-55dBc  
 2.5MHz to 25MHz <-40dBc

#### Non-Harmonic Distortion (typ.):

DC to 15MHz <-70dBc  
 15MHz to 25MHz <-60dBc

#### Total Harmonic Distortion:

DC to 100kHz 0.1%

#### Flatness (1kHz)(typical):

DC to 1MHz 1%  
 1MHz to 25MHz 5%

#### Phase Noise (8 points Sine, Max. SCLK)

100Hz Offset <-103dBc/Hz  
 1kHz Offset <-110dBc/Hz  
 10kHz Offset <-118dBc/Hz  
 100kHz Offset <-124dBc/Hz  
 1MHz Offset <-135dBc/Hz

#### TRIANGLE, RAMP

**Start Phase:** 0 to 360°

**Phase Resolution:** 0.1°

**Timing Ranges:** 0%-99.9% of period

#### SQUARE, PULSE

**Duty cycle:** 1% to 99%

**Timing Ranges:** 0%-99.9% of period

**Rise/Fall time:** <8ns

**Aberration:** <5%

#### SINC (SINE(x)/x)

**"0" Crossing:** 4 to 100 cycles

#### GAUSSIAN PULSE

**Time Constant:** 1 to 200

#### EXPONENTIAL FALL/RISING PULSE

**Time Constant:** -100 to 100

#### DC

**Range:** -5V to 5V

#### DIGITAL PULSE GENERATOR OPTION

**Pulse Mode:** Single or double, programmable

**Polarity:** Normal, inverted, complement

**Period:** 80ns to 1000s

**Resolution:** 20ns

**Pulse Width:** 40ns to 1000s

#### Rise/Fall Time:

Fast <8ns (typ.)  
 Linear 20ns to 1000s

#### High Time, Delay &

**Double Pulse Delay:** 20ns to 1000s

**Amplitude Window:** 10mVp-p to 10Vp-p(1)

Low Level -5V to +4.995V(1)  
 High Level -4.995V to +5V(1)

(1) Double into high impedance

#### NOTES:

**1.** All pulse parameters, except rise and fall times, may be freely programmed within the selected pulse period provided that the ratio between the period and the smallest incremental unit does not exceed the ratio of 512,000 to 1. With the 1M option, the ratio is extended to 1,000,000 to 1, hence the specifications below do not show maximum limit as each must be computed from the above relationship.

**2.** Rise and fall times, may be freely programmed provided that the ratio between the rise/fall time and the smallest incremental unit does not exceed the ratio of 100,000 to 1.

**3.** The sum of all pulse parameters must not exceed the pulse period setting

#### ARBITRARY WAVEFORMS

**Sample Rate:** 100mS/s to 50MS/s

**Vertical Resolution:** 14 Bits

**Waveform Memory:** 512k points standard  
 1M points option (per channel)

**Min. Segment Size:** 16 points

**Resolution:** 4 points

**No. of Segments:** 1 to 2k

#### SEQUENCED ARBITRARY WAVEFORMS

**Operation:** Permits division of the memory bank into smaller segments. Segments may be linked, and repeated in user selectable fashion to generate extremely long waveforms.

**Sequencer steps:** 1 to 2k

**Min. Seg. Duration:** 1μs

**Segment loops:** 1 to 1M

#### ADVANCE MODES

**Automatic:** No triggers required to step from one segment to the next. Sequence is repeated continuously through a pre-programmed sequence table.

**Stepped:** Current segment is sampled continuously, external trigger advances to next programmed segment.

**Single:** Current segment is sampled to the end of the segment including repeats and idles there. Next trigger advances to next segment.

**Mixed:** Each step of a sequence can be programmed to advance either: a) automatic (Automatic mode), or b) with a trigger (Stepped mode)

**Advance Source:** External (TRIG IN), Internal or software

#### MODULATION

##### COMMON CHARACTERISTICS

**Carrier Waveform:** Sine, Triangle, Square, Pulse, Ramp, Sine(x)/x, Gaussian, Exponential, Repetitive Noise, DC and Arb

**Carrier SCLK:** 100mS/s to 50MS/s

**Carrier Frequency:** Waveform dependent

**Resolution:** 12 digits, limited by 1μHz

**Accuracy:** 0.1%

**Freq. Distortion:** <0.1%

#### Modulation Source:

Internal FM, Arbitrary FM, Sweep  
 External AM, FSK

#### FM

**Modulating Shape:** Sine, Square, Triangle / Ramp

**Modulation Freq.:** 1mHz to 100kHz

**Deviation Range:** 100mS/s to 25MS/s

#### ARBITRARY FM

**Modulating Shape:** Arbitrary waveform, 10 to 20000 waveform points

**Modulating SCLK:** 1mS/s to 2MS/s

**Deviation Range:** 100mS/s to 25MS/s

#### AM

**Envelope Freq.:** 1μHz to 500kHz

**Sensitivity:** 0V to +5V (5Vp-p)

**Modulation Depth:** 0% to 100%

# MODELS WW5061/2

## 50MS/s Single/Dual Channel Arbitrary Waveform Generators Specification

### FSK

<b>Type:</b>	Hop or Ramp
<b>Low level:</b>	Carrier sample clock
<b>High level:</b>	Hop frequency
<b>Baud Rate Range:</b>	1bits/sec to 10Mbits/sec
<b>Min. FSK Delay:</b>	1 waveform cycle + 50ns
<b>Ramp FSK:</b>	
Time	10µs to 1s
Resolution	3 digits

### SWEEP

<b>Sweep Time:</b>	1ms to 1000s
<b>Sweep Step:</b>	Linear, Logarithmic or Arb
<b>Sweep Direction:</b>	Up or down

### COMMON CHARACTERISTICS

#### FREQUENCY

<b>Resolution:</b>	
Display	11 digits (limited by 1µHz)
Remote	14 digits (limited by 1µHz)
<b>Accuracy/Stability:</b>	Same as reference

#### ACCURACY REFERENCE CLOCK

Internal	0.0001% (1ppm TCXO) initial tolerance over a 19°C to 29°C temperature range; 1ppm/°C below 19°C and above 29°C; 1ppm/year aging rate
External	10MHz TTL, 50% duty cycle

#### AMPLITUDE

<b>Range:</b>	10mV to 10Vp-p, into 50Ω; Double into open circuit
<b>Resolution:</b>	4 digits
<b>Accuracy (1kHz):</b>	
100mV to 1Vp-p	±(1% + 5mV)
1Vp-p to 10Vp-p	±(1% + 25mV)

#### OFFSET

<b>Range:</b>	0 to ±4.5V
<b>Resolution:</b>	2.2 mV
<b>Accuracy:</b>	1%

#### FILTERS

<b>Type:</b>	12.5MHz / 25MHz Elliptic
--------------	--------------------------

#### OUTPUTS

##### MAIN OUTPUTS

<b>Coupling:</b>	DC coupled
<b>Connector:</b>	Front panel BNC
<b>Impedance:</b>	50Ω, ±1%
<b>Protection:</b>	Protected against temporary short to case ground

### SYNC/MARKER OUTPUT

<b>Connector:</b>	Front panel BNC
<b>Impedance:</b>	50Ω, ±1%
<b>Level:</b>	>2V into 50Ω, 4V into 10kΩ
<b>Validators:</b>	BIT, LCOM
<b>Protection:</b>	Protected against temporary short to case ground
<b>Position:</b>	Point 0 to n
<b>Width:</b>	4 to 100000 points
<b>Resolution:</b>	4 points
<b>Source:</b>	Channel 1

### SAMPLE CLOCK OUTPUT

<b>Connector:</b>	Rear panel SMB
<b>Level:</b>	ECL
<b>Impedance:</b>	50Ω, terminated to -2V

### SINEWAVE OUTPUT

<b>Connector:</b>	Rear panel BNC
<b>Impedance:</b>	50Ω, ±1%
<b>Level:</b>	1V into 50Ω
<b>Protection:</b>	Protected against temporary short to case ground
<b>Source:</b>	Sample clock frequency
<b>Frequency Range:</b>	100mHz to 50MHz
<b>Resolution:</b>	Same as Sample clock
<b>THD:</b>	0.05% to 100kHz
<b>SFDR:</b>	<-30dBc to 50MHz

### INPUTS

#### TRIGGER INPUT

<b>Connector:</b>	Rear panel BNC
<b>Input Impedance:</b>	10kΩ, ±5%
<b>Polarity:</b>	Positive or negative
<b>Threshold Level:</b>	TTL
<b>Min. Pulse Width:</b>	20ns

#### EXTERNAL REFERENCE INPUT

<b>Connector:</b>	Rear panel BNC
<b>Frequency:</b>	10MHz
<b>Impedance &amp; Level:</b>	10kΩ ±5%, TTL, 50% ±5%

#### AM INPUT

<b>Modulation Input:</b>	Rear panel BNC
<b>Impedance:</b>	1MΩ, ±5%
<b>Max. Input Voltage:</b>	12V

#### SAMPLE CLOCK INPUT

<b>Connector:</b>	Rear panel SMB
<b>Input Level:</b>	ECL
<b>Impedance:</b>	50Ω, terminated to -2V
<b>Range:</b>	100mHz to 50MHz
<b>Min. Pulse Width:</b>	4 ns

### SYNCHRONIZATION CONNECTOR

<b>Connector:</b>	Rear panel 9-pin D-SUB
<b>SYNC Cable:</b>	Optional, consult factory at the time of purchase

### RUN MODES

<b>Continuous:</b>	Free-run output of a waveform
<b>Triggered:</b>	Upon trigger, outputs one waveform cycle. Last cycle always completed
<b>Gated:</b>	External signal enables generator. First output cycle synchronous with the active slope of the triggering signal. Last cycle of output waveform always completed
<b>Burst:</b>	Upon trigger, outputs a single or multiple pre-programmed number of waveform cycles from 1 through 1M

### TRIGGER CHARACTERISTICS

<b>System Delay:</b>	1 Sample Clock + 150ns
<b>Trigger Start, Stop &amp; Phase Control:</b>	0 to 512k (1M optional)
<b>Resolution:</b>	4 points
<b>Breakpoint Error:</b>	±4 points
<b>Breakpoint Source:</b>	External, Manual, or command

### EXTERNAL

<b>Connector:</b>	Rear panel BNC
<b>Level:</b>	TTL
<b>Slope:</b>	Positive or negative
<b>Frequency:</b>	DC to 2MHz
<b>Impedance:</b>	10kΩ, DC coupled

### INTERNAL

<b>Range:</b>	100mHz to 2MHz
<b>Resolution:</b>	14 digits, limited by 1µHz
<b>Accuracy:</b>	0.1%

### MANUAL

<b>Source:</b>	Soft trigger command from the front panel or remote
----------------	---

### INTER-CHANNEL DEPENDENCY (WW5062)

**Separate controls:** Output on/off, amplitude, AM, offset, standard waveforms, user waveforms, waveform size, sequence table, channel 2 clock divider, trigger start phase, breakpoints

# MODELS WW5061/2

## 50MS/s Single/Dual Channel Arbitrary Waveform Generators

### Specification

**Common Controls:** SCLK, frequency, reference source, trigger and sequence advance mode, SYNC OUT, FM, FSK, sweep and arm

#### PHASE OFFSET (LEADING EDGE)

**Range:** 0 to 512k points (1M option)  
**Resolution/Accuracy:** 1 point, or 1 SCLK of CH. 2  
**Initial Skew:** <±2ns, with sclk divider = 1;  
 <±3ns, with sclk divider > 1

#### CHANNEL 2 SAMPLE CLOCK DIVIDER

**Range:** 1 to 65,535 points  
**Resolution:** 1 point

#### MULTI-INSTRUMENT SYNCHRONIZATION

#### PHASE OFFSET (LEADING EDGE)

**Range:** 0 to 512k points (1M optional)

**Resolution:** 4 point  
**Initial Skew:** <±15ns, depending on cable length and quality, typically with 0.5 meter coax cables

#### GENERAL

**Voltage Range:** 85 to 265V  
**Frequency Range:** 48 to 63Hz  
**Power Consumption:** 60W max  
**Display Type:** Color LCD, back-lit  
 Size: 3.8" reflective  
 Resolution: 320 x 240 pixels,  
**Interfaces:**  
 USB Device: 1 x rear, USB device, (A type)  
 LAN: 100/10 BASE-T  
 GPIB: IEEE 488.2 standard interface  
**Dimensions:**  
 With Feet: 212 x 102 x 415mm (WxHxD)  
 Without Feet: 212 x 88 x 415mm (WxHxD)  
**Weight:**  
 Without Package: 3.5Kg  
 Shipping Weight: 4Kg  
**Temperature:**  
 Operating: 0 - 50°C  
 Storage: -40°C to + 70°C.  
**Humidity:**  
 11°C to 30°C: 85%;  
 31°C to 50°C: 75%

**Safety:** EN61010-1, 2nd revision  
**Calibration:** 1 year  
**Warranty <sup>(1)</sup>:** 5 years standard

#### ORDERING INFORMATION

MODEL	DESCRIPTION
WW5061	50MS/s Single Channel Arbitrary Waveform Generator
WW5062	50MS/s Dual Channel Arbitrary Waveform Generator

#### OPTIONS

**Option 1:** 1M Memory

#### ACCESSORIES

**Sync Cable:** Multi-instrument synchronization  
**S-Rack Mount:** 19" Single Rack Mounting Kit  
**D-Rack Mount:** 19" Dual Rack Mounting Kit  
**Case Kit:** Professional Carrying Bag

**Note:** Options and Accessories must be specified at the time of your purchase.

<sup>(1)</sup> Standard warranty in India is 1 year.